

Safe Work Procedure

Changing Auger Teeth

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Pinch points Muscle strain Cutting injury/amputation	Steel toed boots Eye protection Face shield Hand protection	

Safe Work Procedure:
<p>1 Wear all applicable PPE</p> <p>2 Beat out the old tooth with a sledge hammer. A pin or piece of rebar may be required to knock out tooth</p> <p>3 Shield yourself while driving in the new tooth</p> <p>3 Keep fingers and hands away from Kelly bar and areas where they can get jammed</p> <p>4 Maintain periodic eye contact with the operator and make sure they are aware when you have completed task</p>

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p> <p>6 Personal Protective Equipment</p> <p>8 Musculoskeletal Injury</p> <p>16 Machines, Tools and Robots</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <hr/> <p>Reviewed By Worker Rep/WSH Committee:</p> <p>Date:</p>
--	--