

Safe Work Procedure

Backfill From Top of a Bank

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Other workers and equipment Machine malfunction Working on loose grounding	Steel toed boots Hard hat Safety glasses Gloves Safety Vest	Operator Training

Safe Work Procedure:
<ol style="list-style-type: none"> 1 Designate a spotter who will be responsible for directing the driver/operator to the bank and to dump load 2 Check ground for stability before proceeding to top of bank 3 Ensure that all other workers and equipment are aware and stay clear of dump 4 Follow through with dump when spotter signals it is safe to do so 5 Once load is completely dumped, lower the box and carefully pull away from the bank

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards: MB Workplace Safety & Health Act & Regulations: 6 Personal Protective Equipment 14 Fall Protection 16 Machines, Tools and Robots 20 Vehicular and Pedestrian Traffic 26 Excavations and Tunnels	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years Reviewed By Worker Rep/WSH Committee: Date:
--	--