

## Safe Work Procedure

### Load Crawler Loader

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Slip/Trip hazard Fall injury Vehicle/Machine damage Pinch points	Steel toed boots Safety glasses Hand protection Hard hat	Operator training

Safe Work Procedure:
<ol style="list-style-type: none"> <li>1 Enter crawling loader using 3 point contact method</li> <li>2 Drive up to back of trailer, making sure you are straight and properly aligned.</li> <li>3 Raise bucket on to deck and use bucket to raise the loader</li> <li>4 Move ahead slowly until front of tracks are on the trailer</li> <li>5 Proceed to the front of the trailer carefully</li> <li>6 Lower bucket and set parking brake</li> <li>7 Exit cab using 3 point contact method</li> <li>8 Dismount trailer by sitting on deck and pushing of. Jumping off trailers is prohibited</li> <li>9 Secure loader with two chains using 4 point contact</li> <li>10 Inspect load and proceed to job</li> </ol>

***If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure***

**REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR**

<p><b>Guidance Documents/Standards:</b></p> <p>MB Workplace Safety &amp; Health Act &amp; Regulations:          4 General Workplace Requirements          6 Personal Protective Equipment          16 Machines, Tools and Robots          22 Powered Mobile Equipment</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <hr/> <p>Reviewed By Worker Rep/WSH Committee:</p>  <p>Date:</p>
---	--