

Safe Work Procedure

Propane Heaters

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Fumes/Exhaust Flammable materials Tripping hazard	Steel toed boots Hearing Protection Hard hat Hand protection Eye Protection	

Safe Work Procedure:
<p>1 Flammable materials (including propane bottle) is to be located a minimum of 50 feet from the front of the heater</p> <p>2 All flammable materials (including propane bottle) is to be located a minimum of 10 feet from the sides, rear and top of the heater</p> <p>3 The heater hose length should not be more than 50 feet</p> <p>4 Extra hose is to be coiled and tied so that it is not a tripping hazard</p> <p>5 Hose lying on the floor in traffic areas should be protected against puncture</p> <p>6 Propane tanks must be stored in a well ventilated and safe, secure place to prevent tipping or any other damage</p> <p>7 Ensure there is sufficient space for the exhaust and ventilation of the heater</p>

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations:</p> <p>2.1 Safe Work Procedures 4 General Workplace Requirements 6 Personal Protective Equipment 35 WHMIS 36 Chemical and Biological Substances</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <hr/> <p>Reviewed By Worker Rep/WSH Committee:</p> <p>Date:</p>
--	--