

Safe Work Procedure

Support Dump Boxes

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Serious injury/potential death Pinch points	Steel toed boots Eye protection Hand protection Hard Hat	

Safe Work Procedure:
<ol style="list-style-type: none"> 1 Park and block truck in neutral with the PTO and pump engaged 2 Raise truck box to desired level 3 A Stiff leg is a permanently attached pivot and rest, and is the preferred method of support 4 If not available use the following: <ul style="list-style-type: none"> A 6"x6"x6' long timberblock across the truck frame between the box and subframe as close as possible to the box hinge B 2 pieces of 4"x4"x6' timber placed vertically between tandem tire and the box C Pin locks provided by the manufacturer to secure the box in the elevated position 5 Only keep the box lifted for as long as possible

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards: MB Workplace Safety & Health Act & Regulations: 4 General Workplace Requirements 6 Personal Protective Equipment 16 Machines, Tools and Robots 22 Powered Mobile Equipment Safe Work Bulletin #148	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years Reviewed By Worker Rep/ WSH Committee: Date:
---	---