

Safe Work Procedure

Unloading Granular

Facility:	Written By:	Approved By:	Date Created	Date of Last Revision:

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Vehicle or property damage Serious injury Pinch points	Steel toed boots Eye protection Hand protection Reflective vest ROPS	

Safe Work Procedure:
<p style="text-align: center; font-weight: bold;">Safe Work Procedure:</p> <ol style="list-style-type: none"> 1 Back up to the dumping location with the use of a spotter 2 Park and ensure brake is applied 3 Exit cab using three point contact and inspect the ground to ensure it is level and firm 4 Roll up tarp 5 Enter cab using three point contact 6 Engage PTO and pump 7 When hoist is lifting, trip the end gate 8 Hoist box to the final stage 9 When load is dumped slowly drive ahead a few feet and lower hoist 10 Disengage pump and PTO and close end gate.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

<p>Guidance Documents/Standards:</p> <p>MB Workplace Safety & Health Act & Regulations: 2.1 Safe Work Procedures 4 General Workplace Requirements 16 Machines, Tools and Robots 22 Powered Mobile Equipment</p>	<p>This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a minimum of every three years</p> <p>Reviewed By Worker Rep/ WSH Committee:</p> <p>Date:</p>
--	--